

MS Series Technical Details

MS Series	Cutting Capacity	Cutting Length	Cutting Angle	Stroke / min.	Motor Power	Back Gauge Distance (Std.)	Table Width	Table Height	Height	Width	Length	Weight
	mm	mm		1/min.	kW	mm	mm	mm	mm	mm	mm	~kg
1303	3	1350	2° 30'	35	3	550	400	850	1260	1350	1900	1060
2003	3	2050	2° 12'	35	3	550	400	850	1260	1350	2600	1280
2525	2,5	2550	1° 40'	35	3	550	400	850	1260	1350	3100	1540
2004	4	2050	1° 30'	42	7,5	750	450	800	1350	2300	2700	2800
2504	4	2550	1° 30'	42	7,5	750	450	800	1350	2300	3200	3230
3004	4	3100	1° 30'	42	7,5	750	450	800	1350	2300	3700	3730

*Capacity tested with St 37

Standard & Optional Equipment

Standard Equipments

Heavy duty St44 Al steel construction & Stress reliever frame	
Easy blade gap adjustment	(MS 2004, MS 2504, MS 3004)
Finger protect	
Hold down with rubbers	
Manual back gauge	(MS 1303, MS 2003, MS 2525)
Motorized back gauge with ballscrew	(MS 2004, MS 2504, MS 3004)
Ball integrated front tables	(MS 2004, MS 2504, MS 3004)
Top blades with 2 sides, Bottom blades with 2 sides	(MS 1303, MS 2003, MS 2525)
Top blades with 2 sides, Bottom blades with 4 sides	(MS 2004, MS 2504, MS 3004)

Optional Equipments

CE-Norm for EU
NC Touchscreen control unit (D-Touch 7)
Cutting line with shade wire (MS 2004, MS 2504, MS 3004)
Curtain light guards
Special back gauge: Motorized back gauge with ballscrew (750 mm or 1000 mm)
Pneumatic thin sheet support system (Suitable for machines with 750mm back gauge)
Adjustable angle stop 0-180°
Add. Support extra arms
Special blades
Overseas special packing