



KDG 700x1250 DM DOUBLE COLUMN SEMI AUTO MITREBAND SAW MACHINE

*Photo may feature machine with optional accessories



CUTTING CAPACITY

	0°	30°	45°	60°	-30°	-45°
Ø	700 mm	700 mm	700 mm	480 mm	700 mm	700 mm
\Box	700 mm	700 mm	700 mm	480 mm	700 mm	700 mm
	700 x 1250 mm	700 x 1100 mm	700 x 900 mm	700 x 500 mm	700 x 1000 mm	700 x 800 mm

TECHNICAL SPECIFICATIONS

Main Motor : 7,5kW

Gearbox : Bevel Helical PKD 4390 High Efficiency

Hydraulic Motor : 1,5kW

Hydraulic Tank Capacity : 35 Liters

Coolant Motor : 0,2kW

Coolant Tank Capacity : 50 liters

Conveyor Motor : 0,12kW

Swarf Brush Motor : 0,25kW

Blade Speed : 25-90 m/min

Blade Dimensions : 8.520x54x1,6 mm

Machine Weight : 5500 kg

Machine Dimensions : 1950x4400 x2500 mm

Table Height : 870 mm

STANDARD ACCESSORIES

Frequency Inverter

Easy variable adjustable band speed visible at the screen



Easy Use Control Panel

Buttons directly to use for each functionality

Buttons at keybord folioEmergency stop button



Digital Screen

It Shows All Alarms and Directives



Sensible Cutting Feed Adjustment

Provides to adjust bow down speed.



Sensible Cutting Feed Pressure Adjustment

Provides to adjust bow down pressure.



Full Stroke Hydraulic Clamping Vise

Pressure, clamping period and clamping time can be adjusted.



Adjustable Clamping Pressure of Vise

Controlled visibly by manometer



Special Designed Vice Jaw for

Clamping Materials at Various Degree Position




Hydraulic Top Clamping Vise

Holds the workpiece vertically with hydraulic power during cutting operation and provides bundle cutting. Simply to switch on\off by using the valve



Hydraulic Blade Tensioning

Automatic controlling of bands tensioning



Swarf Conveyor

Spiral conveyoring system easy to clean and electronical time controlled



Adjustable Down and Top Limit Switch

Material height adjustment to save time on frame feeding.



Down Motion With Roller Type Linear Guide

Roller type lineer guides for easy movement of frame, long life design



Guide Arm Motion With Linear Guide

Roller type lineer guides for simple guide arm positioning ,long life design




Simple Adjustable Guide Arm



Band Guides

Large with carbide insert Triple bearings on both side and Carbide Plate To cover all band width



Wheels Strong Construction With Large Bearings



Special Construction For Tensioning Wheel



Laser Line

To make cutting line visible before cutting




Motorized Swarf Brush



Special Table Construction

Inserted rollers to make easy move of material.



Manometer



Wheel Turn Control By Proximity Switch





Miter Position Holder by Hydraulic Brake

Clamp and unclamp by using button

Miter positining manual, motorized as option



Door Opener By Gas Spring



Transportation Support By Lifting Eye



Workplace Lightning by LED



Coolant Oil Level Indicator




Hydraulic Oil Level Indicator





Easy to Read The Miter Cut Degree Indicator

Digital at screen as option



Limited Moveable Control Panel Box



Transport Hooks



Levelling Foot Leg




Rotating Table



Custom-made jaw



Blade Bedding with 3 Bearings and Carbide Plate



Bevel Helical Gearbox



Cover Switch



Tension Switch



Electric Cabinet Switch





2 pcs 3 mt Roller Table

Special construction infeed and output roller table each 3 meter special designed with respect to miter cutting -45° up to $+60^{\circ}$



Automatic Stop when;

- ➤ The covers are open
- ➤ Blade tension is low or broken
- ➤ Blade is blocked
- ➤ Additional alarms by giving codes

OPTIONAL ACCESSORIES


Micro Mist Coolant System

By choosing this option the button for selecting coolant makes automatically change from water to micro mist



Digital Miter Angle Indicator

Display visibility for each degree recommended to use motorized miter adjustment .(KDG-Z)







Motorized Feed Table

Depending lenght special inquary needed










SAFETY EQUIPMENTS



1-2	Lid Safety Switch
3	Top Limit Switch
4	Down Limit Switch
5	Proximity Switch
6	Break Off Switch
7	Electricity Panel Cover Switch

TERMS

Delivery (After Receipt of written PO):

Type of Delivery :Exwork

WARRANTY CONDITIONS

The machine is under the warranty of KARMETAL LTD. ŞTİ. For a period of 2 years for mechanical parts, 1 year for electric and electronic parts from the date of purchase. This warranty is subject to all of the terms and conditions listed below:

- 1. This warranty is valid only if the **Warranty Registration Form** is filled in and returned to the manufacturer or its authorized dealer within two months after the date of purchase.
- 2. The obligation of the manufacturer under this warranty shall be limited to repairing or replacing components which proves defective and which our examination shall disclose to our satisfaction to be defective.
- 3. Defects due to improper operation, misuse, neglect, alteration, irregular voltage conditions, inadequate wiring, improper installation (all electrical and electronic components, all electrical motors etc.) and due to accidents or any damage caused by transportation, flood, fire, natural disasters, theft are not included in this warranty and are strictly the responsibility of the purchaser.
- 4. Any part returned to KARMETAL or its authorized dealer under the terms of this warranty shall be on the basis of transportation charges prepaid by the customer and must be accompanied by a record of the machine model code and serial number.
- 5. This warranty does not apply to the following components; band saw blade, blade pressure pads or brackets and blade guide bearings because of being consumables.
- 6. Manufacturer and authorized dealer cannot be blamed within maximum repair period for the material or moral damage. Apart from that act the period as Warranty Conditions and there will not be done any retroactive requirement.





Fax: +90 264 276 59 19

www.karmetal.com.trsales@karmetal.com.tr

Machine videos are available on:







